






DIST	COUNTY	ROUTE	KILOMETER POST TOTAL PROJECT	SHEET TOTAL NO. SHEETS
REGISTERED ELECTRICAL ENGINEER			Sampol No. E-13633 EXPIRATION DATE 8-30-02 ELECTRICAL STATE OF CALIFORNIA	
JULY 1, 1999 PLANS APPROVAL DATE				
The State of California or its officers or agents shall not be responsible for the accuracy or completeness of electronic copies of this plan sheet.				



WIRING DIAGRAM

NOTES

- The telephone demarcation cabinet shall be furnished with a mounting panel, outlets and breaker and deadfront plates in place. All dimensions are nominal.
- An approved mastic or caulking compound shall be placed on the foundation, prior to placing the pedestal, to seal all openings between the bottom of the pedestal and the foundation.
- In unpaved areas, a raised PCC pad shall be placed in front of the telephone demarcation cabinet. Pad shall be 610 mm x 560 mm x 100 mm thick, with 50 mm above the finished grade.
- All conduits, anchor bolts and enclosure cabinet shall be grounded and bonded to the ground rod.
- Telephone demarcation cabinet:
 - Material shall be anodized aluminum (3.2 mm thick).
 - Fabrication shall conform to the requirements of Section 86-3044, "Cabinet Construction", of the Standard Specifications.
 - The exterior door shall be side hung and secured with a padlockable draw latch, the padlock hole shall be a minimum diameter of 11 mm to receive a State-furnished padlock.
 - Venting louvers shall be located on the door.
 - Fan shall be mounted in ventilator housing.
 - Fan shall be thermostatically controlled and manually adjustable to turn on between 32°C and 65°C.
 - Fan circuit shall be fused at 175 percent of the fan motor capacity.
 - Fan capacity shall be at least 0.7 m³ per minute.
 - Fasten fixed mounting panels with nuts, lock and flat washers to 5 mm ø x 25 mm studs welded to enclosure.



SIGNAL LIGHTING AND ELECTRICAL SYSTEMS TELEPHONE DEMARCATION CABINET TYPE B

NO SCALE
ALL DIMENSIONS ARE IN
MILLIMETERS UNLESS OTHERWISE SHOWN